(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 11 January 2001 (11.01.2001)

PCT

(10) International Publication Number WO 01/02508 A1

(51) International Patent Classification⁷: C09J 7/02

(21) International Application Number: PCT/US00/17457

(22) International Filing Date: 23 June 2000 (23.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 11/189081 2 July 1999 (02.07.1999) JP

(71) Applicant (for all designated States except US): 3M INNOVATIVE PROPERTIES COMPANY [US/US]; 3M Center, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): YAMANAKA, Keizo [JP/JP]; Nihonmatsu 4-28-2-102, Sagamihara-city, Kanagawa 229-1137 (JP). FUKUSHI, Tatsuo [JP/JP]; 2-9-45, Higashifuchinobe, Sagamihara-city, Kanagawa 229 (JP). TAKAMATSU, Yorinobu [JP/JP]; 11-7, Kamimizo 3-chome, Sagamihara-city, Kanagawa 229-1123 (JP).

(74) Agents: GOVER, Melanie, G. et al.; Office of Intellectual Property Counsel, P.O. Box 33427, Saint Paul, MN 55133-3427 (US).

(81) Designated States (national): KR, US.


(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published:

With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PRESSURE SENSITIVE ADHESIVE SHEET AND PRODUCTION METHOD THEREOF



(57) Abstract: Problem to be solved: to provide a simple method for improving the adhesive property between a fluorine-containing material substrate and a pressure sensitive adhesive which are poor in the adhesion to each other. Means to solve the problem: when a fluorine-containing material substrate having coated thereon a pressure sensitive adhesive is irradiated with an electron beam, a chemical bond is formed between the substrate and the pressure sensitive adhesive. Furthermore, the pressure sensitive adhesive can be cured by polymerization and also the substrate can be cross-linked.

THE TO SELECT THE SELECT STREET OF THE SELECT STREET STREE

01/02508 A1